



ELECTRICAL:
 CURRENT RATING: 1.5A
 CONTACT RESISTANCE:
 < 20 mΩ Max.
 INSULATION RESISTANCE:
 > 10 MΩ Min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 1000V (rms) AC for 1 Minute

MATERIAL:
 INSULATOR: ABS Resin
 CONTACT: 0.45mm Dia. Phosphor Bronze Alloy, 6u" Gold Plating over Nickel Plating

HOW TO ORDER:
M 0 0 7 - X X 1 0 - 3 0 X - Z

P: NUMBER OF POSITIONS
 C: NUMBER OF CONTACTS:
 64 - 6P4C
 66 - 6P6C
 86 - 8P6C
 88 - 8P8C
 68 - 8P6C (1 SIDE) / 8P8C (1SIDE)

MODULAR TYPE:
 1 - 3-WAY

COLOR:
 3 - IVORY

FOR 2-WAY & 3-WAY WIRING:
 1 - STRAIGHT
 2 - CROSSED

RoHS COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	A.M.	S.M.	S.M.	6/15/99
A	WHS	S.M.	S.M.	08/09/06
SCALE	N/A	MAT'L	FINISH	
TOL. DEC.	.X +/- 0.25	.XX +/- 0.13	.XXX +/- 0.05	ANGLE +/- UNIT: mm

SMP TECHNOLOGY, INC.

MODULAR COUPLER JACK

SERIES: M007-XX1X-XXX-Z

Pg: 1