



Pin Assignments

1	1	1
3	3	3
4	4	4
5	5	5
6	6	6
7	7	7
*	*	*
*	*	*
18	18	18
21	21	21
23	23	25
27	27	27
28	28	28
29	29	29
31	31	31
32	32	32
33	33	33
34	34	34
35	35	35
36	36	36
37	37	37
38	38	38
39	39	39

Ground Pin

2	2	2
19	19	19
22	22	22
24	24	24
26	26	26
30	30	30
34	40	40

- 100 % Open Short
- Contact Resistance 20 Milliohms
- Hi Pot: 300 V 10 Milliseconds
- Insulation Resistance: 20 Megaohms
- Connectors ATA; 40 Pos. (3)
- Cable: UL20276 30AWG;
- Overmold :PVC

HOW TO ORDER:

C 0 0 3 2 4 7 - X X - Z

**RoHS
COMPLIANT**

COLOR:
A - RED
B - GRAY
C - YELLOW
D - BLUE
E - BLACK

TOTAL LENGTH
1 - 450mm
2 - 600mm

A	B
300mm	150mm
400mm	200mm

Other Lengths Available

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	6/21/07

SMP TECHNOLOGY, INC.

SCALE: N/A

Cable Ass'y, Round ATA ; 3 Connectors

TOL. DEC. Overall Length +/- 20 mm; "A" & "B" +/- 10 mm

UNIT: mm

P/N: C003247XX-Z

Pg: 1