



TABLE A

Part No.	Length (mm)	Part No.	Length (mm)
C003253-1-Z	152	C003253-6-Z	406
C003253-2-Z	203	C003253-7-Z	457
C003253-3-Z	254	C003253-8-Z	508
C003253-4-Z	305	C003253-9-Z	559
C003253-5-Z	356	C003253-0-Z	610

Electrical Specifications

100 % Test ; Open and Short Circuit  
Hi - Pot Test : 300 V / 10 ms.

⑤	Netting	2 pcs	Black $\phi$ 7 mm;
④	H.S.Tubing	2 pcs	30 x 56 mm.
③	Connector	1 Piece	ATA Connector ; 40 pos.;w/SR; Polarized ( Black)
②	Connector	1 Piece	ATA Connector ; 40 pos.;w/SR; Polarized ( Blue)
①	Cable	1 Piece	UL 20276; 30 AWG ; 40 Pos ( Color Wire)
No.	Name	Qty	Description

HOW TO ORDER:

C 0 0 3 2 5 3 - X - Z

TOTAL LENGTH

See Table A

RoHS  
COMPLIANT

Rev	Drawn	Checked	Approved	Date	SMP TECHNOLOGY, INC.
0	Issued	B.S.	S.M.	8/23/07	
SCALE: N/A					Cable Ass'y, Round ATA ; 2 Connectors
TOL. DEC.					UNIT: mm
P/N: C003253-X-Z					Pg: 1