



Electrical Character:
 100% Open/Short.
 Contact Resistance:2 ohms.
 Hi-Pot:300V 10ms.
 Insulation Resistance:10m ohms.

HOW TO ORDER:

C 0 0 3 2 5 4 - X - Z

**RoHS
COMPLIANT**

TOTAL LENGTH

1 - 450mm
 2 - 600mm

| A | B |
|-------|-------|
| 300mm | 150mm |
| 400mm | 200mm |

Other Lengths Available

| | | | | |
|-----|---------|-------|---|---------------------|
| ⑥ | PET Web | 2pcs | Black | ∅4mm |
| ⑤ | Sleeve | 4pcs | Black | ∅12mm*L30mm |
| ④ | Conn | 1Sets | ATA 40P Black (W/Key 20Pin) | |
| ③ | Conn | 1Sets | ATA 40P Grey (W/Key 20Pin) | |
| ② | Conn | 1Sets | ATA 40P Blue (W/Key 20Pin) | |
| ① | Cable | 1pcs | UL20276 30AWG 40Pairs (1PR:Red/White,39Prs:Color) | Color Cable L=520mm |
| No. | Name | Q'Ty | Description | |

| Rev | Drawn | Checked | Approved | Date | SMP TECHNOLOGY, INC. | |
|--|--------|---------|----------|---------|---------------------------------------|------------------|
| 0 | Issued | B.S. | S.M. | 8/23/07 | | |
| SCALE: N/A | | | | | Cable Ass'y, Round ATA ; 3 Connectors | |
| TOL. DEC. Overall Length +/- 20 mm;"A" & "B" +/- 10 mm | | | | | UNIT: mm | P/N: C003254-X-Z |
| | | | | | Pg: 1 | |