



P1	P2
1	1
2	2
3	3
10	16
11	15
12	14
13	13
14	12
15	11
16	10
32	32
33	33
34	34

TABLE A

Part No.	Length (mm)
C003284-1-Z	229
C003284-2-Z	254
C003284-3-Z	279
C003284-4-Z	305
C003284-5-Z	330

TABLE A

Part No.	Length (mm)	Part No.	Length (mm)
C003284-6-Z	356	C003284-A-Z	483
C003284-7-Z	381	C003284-B-Z	508
C003284-8-Z	406	C003284-C-Z	533
C003284-9-Z	432	C003284-D-Z	559
C003284-0-Z	457	C003284-E-Z	584

Electrical Specifications

100 % Test ; Open and Short Circuit
Hi - Pot Test : 300 V / 10 ms.

⑤	Netting	1 pcs	Black Nylon; ϕ 7 mm;
④	H.S.Tubing	2 pcs	8.0 ϕ x 35 mm.
③	Connector	1 Piece	IDC Connector ; 34 pos. ;w/SR; Polarized; 2.54 mm
②	Connector	1 Piece	IDC Connector ; 34 pos. ;w/SR; Polarized; 2.54 mm
①	Cable	1 Piece	UL 20276; 28 AWG ; 34 Pos
No.	Name	Qty	Description

HOW TO ORDER:

C 0 0 3 2 8 4 - X - Z

TOTAL LENGTH
See Table A

RoHS
COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	Issued	B.S.	S.M.	8/23/07

SMP TECHNOLOGY, INC.

SCALE: N/A

Round Cable Ass'y; 34 Pos. IDC to 34 Pos. IDC

TOL. DEC.

UNIT: mm

P/N: C003284-X-Z

Pg: 1