

RECOMMENDED P.C.B. LAYOUT

DIMENSION(mm)

CONTACTS	A	B	C	D	E	F	G
15	16.33	24.99	30.81	19.28	7.04	2.29	0.89
26	24.66	33.32	39.14	27.51	6.88	2.29	0.64
44	38.38	47.04	53.04	41.28	6.88	2.29	0.64
62	54.84	63.50	69.32	57.71	6.99	2.41	0.62

HOW TO ORDER:

A 1 6 2 - X X 0 4 - X X X - X - Z

CONTACT TYPE:
2 - MALE

NUMBER OF CONTACTS:
15
26
44
62

PLATING OVERALL:
0 - FULL Au
4 - 10u" Au
5 - 15u" Au
7 - 30u" Au
8 - FULL TIN

INSULATOR COLOR:
BLANK - BLACK
1 - WHITE
2 - BLUE
3 - GRAY

MOUNTING OPTION:
SEE PAGE 2

SELECTIVE PLATING:
1 - Au CONTACT AREA/TIN TAIL
9 - 15u" Au CONTACT AREA/TIN TAIL
A - 30u" Au CONTACT AREA/TIN TAIL

RoHS COMPLIANT

ELECTRICAL:

CURRENT RATING: 5A
 CONTACT RESISTANCE: < 30m Ω
 INSULATOR RESISTANCE: > 1000M Ω
 DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC FOR 1 MIN.
 OPERATING TEMPERATURE: -55° C TO +105° C

MATERIAL:

CONTACT: COPPER ALLOY
 INSULATOR: PBT & 30% GLASS FIBER (UL94V-0); COLOR: BLACK-STANDARD
 SHELL - NICKEL PLATED STEEL

Rev	Drawn	Checked	Approved	Date
0 Issued	S.E.	S.M.	S.M.	10/1/97
A Revised for RoHS Compliance	B.S.	S.M.	S.M.	6/12/07

SMP TECHNOLOGY, INC.

SCALE: N/A

D-SUB CONNECTOR, HIGH DENSITY, STRAIGHT, PCB MOUNT, MALE


TOL. DEC. .X +/- 0.25 .XX +/- 0.15 .XXX +/- 0.05 ANGLE +/- 1° UNIT: mm

P/N: A162-XX04-XXX-X-Z

A031 & A032 MOUNTING OPTIONS


MOUNTING OPTION 10

3.05 MM DIAMETER NON-THREADED MOUNTING HOLE




MOUNTING OPTION 11 :

RIVETED 4-40 UNC SCREW LOCK 4.0 mm ON BACK SIDE OF SHELL




MOUNTING OPTION 12 :

RIVETED 4-40 UNC SCREW LOCK ON FRONT SIDE OF SHELL




MOUNTING OPTION 14 :

4.1 mm RIVETED 4-40 SCREW LOCK ON BOTTOM SIDE OF SHELL



MOUNTING OPTION 16 :


3.5 mm RIVETED 4-40 SCREW LOCK ON BOTTOM SIDE OF SHELL



* For Mounting Options 11, 12 & with Nylok installed on inside threads - replace the "1" with the letter L. Example: Option 11 with Nylok installed - use mounting option L1.


MOUNTING OPTION 17 :

RIVETED 4-40 UNC SCREW LOCK ON FRONT SIDE OF SHELL




MOUNTING OPTION 19 :

RIVETED 4-40 UNC SCREW LOCK 5.8mm ON BACK SIDE OF SHELL




MOUNTING OPTION 20:

RIVETED 5.80 mm 4-40 UNC SCREW LOCK ON BACK SIDE OF SHELL; 5.80 mm UNC SCREWLOCK ATTACHED TO FRONT SIDE OF SHELL




MOUNTING OPTION 21:

RIVETED 5.80 mm 4-40 UNC SCREW LOCK ON BACK SIDE OF SHELL; 4.80 mm UNC SCREWLOCK ATTACHED TO FRONT SIDE OF SHELL



MOUNTING OPTION 22:

RIVETED 5.80 mm 4-40 UNC SCREW LOCK ON BACK SIDE OF SHELL;



MOUNTING OPTION 23:

RIVETED 5.80 mm 4-40 UNC SCREW LOCK ON BACK SIDE OF SHELL;

