



MATERIAL:

INSULATOR: Thermoplastic UL94V-0;PBT 30 % Glass Fill

CONTACT: Copper Alloy

CONTACT PLATING: Specified Gold Thickness in Contact Area;

80 μ " Tin on remainder of contact;

All over 30 μ " Nickel Subplate

SHELL: 30 mm thick steel

SHELL PLATING: 80 μ " Nickel over 30 μ " copper

PACKAGING : Inner Tray ; 120 pcs / tray ; Tray Weight - 70.5 grams

Outer Carton; 40 trays (4800 pcs)

Carton Net Weight :6.2 Kg.

9.641 Kg.Carton Gross Weight

HOW TO ORDER:

U 0 0 1 - 0 4 J 0 - F 1 1 - Z

NUMBER OF CONTACTS:

04 - 4 PIN SINGLE PORT

INSULATOR COLOR:

0 - BLACK

of LOCKS

1- 4 Locks

RoHS Compliant

SELECTIVE CONTACT PLATING:

1 - Gold

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	07/09/14

SMP TECHNOLOGY, INC.

USB CONNECTOR, SINGLE PORT, STRAIGHT, THRU HOLE

TYPE J (11.3mm Height), HIGH SPEED 2.0

TOL. DEC. .X +/- 0.30 .XX +/- 0.20 .XXX +/- ANGLE +/- 3° UNIT: mm

P/N: U001-04J0-F11-Z

Pg: 1