



IP67

ACCORDING TO IEC 60529:2001-02
 DEGREES OF PROTECTION:
 - Totally protected against dust
 - Protected against the effect of temporary immersion for 30 min. in 1-meter depth of water

ELECTRICAL:

CURRENT RATING: 1.5A Min.
 CONTACT RESISTANCE:
 < 20 Milliohm Max.
 INSULATION RESISTANCE:
 > 500 Megaohm Min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 1000V (rms) AC for 1 Minute
 OPERATING TEMPERATURE: -10° C to +60° C

MATERIAL:

MAIN HOUSING: Black Thermo Plastic, UL94V-0
 CONTACTS: .46mm Diameter, Phosphor Bronze, 50 u" Gold Plating
 HEX NUT: Black Thermo Plastic
 RJ45 SHIELD: .25mm Thick Copper Alloy, Nickel Plated

HOW TO ORDER:

W R 0 0 - 0 0 2 1 - 0 0 3 0 - Z

REAR TERMINATION:

0 - Coupler

RoHS
COMPLIANT

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	05/02/12

SMP TECHNOLOGY, INC.
 RJ45, Panel Mount Coupler, CAT 6, All Plastic Body, With Dust Cap