



**IP67**

ACCORDING TO IEC 60529:2001-02  
 DEGREES OF PROTECTION:  
 - Totally protected against dust  
 - Protected against the effect of temporary immersion for 30 min. in 1-meter depth of water

**ELECTRICAL:**

CURRENT RATING: 1.5A Min.  
 CONTACT RESISTANCE:  
 < 20 Milliohm Max.  
 INSULATION RESISTANCE:  
 > 500 Megaohm Min.  
 DIELECTRIC WITHSTANDING VOLTAGE:  
 1000V (rms) AC for 1 Minute  
 OPERATING TEMPERATURE: -10° C to +60° C

**MATERIAL:**

MAIN HOUSING: Black Thermo Plastic, UL94V-0  
 CONTACTS: .46mm Diameter, Phosphor Bronze, 50 u" Gold Plating  
 HEX NUT: Black Thermo Plastic  
 RJ45 SHIELD: .25mm Thick Copper Alloy, Nickel Plated

**HOW TO ORDER:**

W R 0 0 - 0 0 2 2 - 0 0 3 0 - Z

REAR TERMINATION:

0 - Coupler

RoHS  
COMPLIANT

Rev	Drawn	Checked	Approved	Date	<b>SMP TECHNOLOGY, INC.</b>
0 Issued	B.S.	S.M.	S.M.	05/02/12	
					RJ45, Panel Mount Coupler, CAT 6
					Rear Termination, IP67, Without Dust Cap
TOL. DEC.	.X +/- 0.38	.XX +/- 0.25	.XXX +/- 0.10	ANGLE +/-	UNIT: mm
					P/N: WR00-0022-0030-Z
					Pg: 1