



**Specifications:**

Input voltage  
 Input voltage  
 Input frequency  
 Output voltage  
 Output current  
 Output power range  
 Over voltage protection  
 Over current protection  
 Short Protection  
 Load Regulation  
 Operating temperature  
 Storage temperature  
 Relative humidity  
 Efficiency  
 Insulation resistance  
 Withstand voltage  
 Safety requirements

**SBD Series:**

100-240 VAC (Limits: 90-246VAC)  
 100-120 VAC (Limits: 90-132VAC)  
 50 to 60 Hz (Limits: 47-63 Hz)  
 See Table On Page 2  
 See Table On Page 2  
 See Table On Page 2  
 120%  
 120%  
 Auto Recovery  
 5%  
 0° C ~ 40° C  
 -20° C ~ +85° C  
 5% ~ 95% non-condensing  
 70% minimum  
 DC500V, 100M Ohm (Min .)  
 2000 VAC / Min. from input to output, 10mA (Max.)  
 PSE-MARK, UL, CUL, CE, CB, UV/GS,  
 UK, CCC, C-TICK, EK-MARK, BSMI,PSB  
 1 year

Warranty

<b>SMP TECHNOLOGY, INC.</b>	
DESKTOP SWITCHING POWER SUPPLY, 9 - 18 WATT,	
VENTLESS, PLUG-IN POWER SUPPLY, STRAIGHT, PLUG-IN [US]	
SERIES:SBD	Pg: 1

MODEL	INPUT	OUTPUT VOLTAGE	OUTPUT CURRENT	POWER OUTPUT	DIMENSIONS
SBD203	AC 100~240V (50/60Hz)	3V	3V/3A	9W	FIG1
SBD203		3.3V	3.3V/3A	10W	FIG1
SBD205		5V	5V/2.6A	13W	FIG1
SBD205		5V	5V/3A	15W	FIG1
SBD206		6V	6V/2.8A	17W	FIG1
SBD209		9V	9V/2A	18W	FIG1
SBD212		12V	12V/1.5A	18W	FIG1
SBD215		15V	15V/1.2A	18W	FIG1
SBD224		24V	24V/0.75A	18W	FIG1

FOR OUTPUT PLUG TABLE  
SEE PAGE 3

<b>SMP TECHNOLOGY, INC.</b>	
DESKTOP SWITCHING POWER SUPPLY, 9 - 18 WATT,	
VENTLESS, PLUG-IN POWER SUPPLY, STRAIGHT, PLUG-IN [US]	
SERIES:SBD	Pg: 2

# STRAIGHT

MALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
	SM1A	ø2.5		11	#22 #24
	SM2A	ø3.5		14	#22 #24

MALE PLUG STRAIGHT (parallel/coaxial cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
	SM2B	ø3.5		14	#22 #24

FEMALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF2A	ø3.5	ø1.3	7	#22 #24
	SF2B	ø3.5	ø1.3	9.5	#22 #24
	SF2C	ø3.5	ø1.3	11	#22 #24
	SF2D	ø3.5	ø1.3	14	#22 #24
	SF3A	ø5.0	ø2.1	9.5	#20
	SF3B	ø5.0	ø2.1	11	#20
	SF3C	ø5.0	ø2.1	14	#20
	SF5C	ø5.5	ø2.5	9.5	#18,#20
	SF5B	ø5.5	ø2.5	11	#18,#20
SF5A	ø5.5	ø2.5	14	#18,#20	
SF6A	ø6.5	ø3.0	9.5	#20	
SF6B	ø6.5	ø3.0	11	#20	

FEMALE PLUG STRAIGHT (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF3D	ø5.0	ø2.1	9.5	#22 #24
	SF3E	ø5.5	ø2.1	11	#22 #24
	SF5D	ø5.5	ø2.1	9.5	#22 #24
SF5E	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG STRAIGHT (parallel cord #20,#22,#24 /Coaxial #22)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF5F	ø5.5	ø2.1	9.5	#20,#22,#23
	SF5G	ø5.5	ø2.1	11	#20,#22,#23
	SF5H	ø5.5	ø2.5	9.5	#20,#22,#23
SF5I	ø5.5	ø2.5	11	#20,#22,#23	

FEMALE PLUG STRAIGHT (SPT-1#18 & XTW-A #20 Cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
SF5J	ø5.5	ø2.1	12.5	#18,#20	

FEMALE PLUG STRAIGHT (parallel/coaxial cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	SF5K	ø5.5	ø2.1	9.5	#22 #24
	SF5L	ø5.5	ø2.1	11	#22 #24
	SF5M	ø5.5	ø2.1	14	#22 #24
SF5N	ø5.5	ø2.5	11	#22 #24	

## MINI DIN MALE PLUG, STRAIGHT

	Part Number	Pin Configuration
	SMD3	
	SMD4	
	SMD5	
	SMS5	
	SMD6	
	SMD7	

# RIGHT ANGLE

FEMALE PLUG RIGHT ANGLE (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF4A	ø5.03	ø1.57	8.2	#22 #24
	RF4B	ø5.03	ø1.57	13.5	#22 #24
	RF3A	ø5.0	ø2.1	9	#22 #24
	RF3B	ø5.0	ø2.1	11	#22 #24
	RF3C	ø5.0	ø2.5	11	#22 #24
	RF5A	ø5.5	ø1.3	11	#22 #24
	RF5B	ø5.5	ø2.1	9.5	#22 #24
	RF5C	ø5.5	ø2.5	9.5	#22 #24
	RF5D	ø5.5	ø2.1	11	#22 #24
RF5E	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG RIGHT ANGLE (parallel cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF2A	ø3.5	ø1.3	9	#22 #24
	RF2B	ø3.5	ø1.3	11	#22 #24
	RF5F	ø5.5	ø2.1	9.5	#22 #24
	RF5G	ø5.5	ø2.1	11	#22 #24
	RF5H	ø5.5	ø2.5	9.5	#22 #24
RF5I	ø5.5	ø2.5	11	#22 #24	

FEMALE PLUG RIGHT ANGLE (Coaxial cord)

	Part Number	D +/-0.1	d+/-0.1	L+/-0.5	Wire Gauge
	RF5J	ø5.5	ø2.1	9.5	#22 #24
	RF5K	ø5.5	ø2.1	11	#22 #24
	RF5L	ø5.5	ø2.5	9.5	#22 #24
RF5M	ø5.5	ø2.5	11	#22 #24	

MALE/FEMALE PLUG RIGHT ANGLE (Parallel cord)

	Part Number	D +/-0.1		L+/-0.5	Wire Gauge
RM2A	ø3.5		16.5	#22 #24	

## MINI DIN MALE PLUG, RIGHT ANGLE

	Part Number	Pin Configuration
	RMD3	
	RMD4	
	RMD5	
	RMS5	
	RMD6	
	RMD7	

### OUTPUT PLUG TABLE